

# PATENT APPLICATION

## METHODS FOR MANAGING HOST ADAPTER SETTINGS

INVENTORS: Guido Maffezzoni  
338 Henderson Drive  
San Jose, California 95123  
Citizen of Italy

ASSIGNEE: ADAPTEC, INC.  
691 S. Milpitas Boulevard  
Milpitas, CA 95035

MARTINE PENILLA & KIM, LLP  
710 Lakeway Dr., Suite 170  
Sunnyvale, California 94085  
Telephone (408) 749-6900

# METHODS FOR MANAGING HOST ADAPTER SETTINGS

*by Inventor*

*Guido Maffezzoni*

## **BACKGROUND OF THE INVENTION**

5

### **1. Field of the Invention**

The present invention relates generally to host adapters attached to computer systems, and more particularly to methods for accessing and managing the configuration and implementation settings of host adapters attached to computer systems.

10

### **2. Description of the Related Art**

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
21

peripheral devices for managing data in multiple formats. Therefore, in order to increase flexibility, it is desirable to increase the connectivity of a computer system.

In order to increase connectivity, computer systems are typically configured with expansion slots capable of receiving a variety of circuit boards that have various functions. Among the type of circuit boards which may be inserted include network interface cards (NICs) which allow the computer to connect to a network, and host adapters which allow computer systems to be configured with one or more local peripheral devices. The most commonly used host adapters are DMA or Ultra-DMA host adapters which are capable of supporting up to four peripheral devices on two channels with two devices per channel, and small computer system interface (SCSI) host adapters which can support up to thirty peripheral devices. Once peripheral devices are connected to the host adapter and appropriately configured, the peripheral devices are integrated into the computer system.

The plurality of devices of a computer system, both on-board system devices and peripheral devices, require specific settings and configurations in order to properly operate as an integrated system. By way of example, a computer system may contain a processor, a mother board, memory, a hard disk drive, a floppy drive, a monitor, a keyboard, a mouse, a printer, a modem, speakers, and all of the necessary interface boards and enhancement devices to assimilate and coordinate the various devices to operate as a computer system. If the computer system is configured with Microsoft Windows95<sup>TM</sup> or newer operating systems, a user can open a graphical user interface (GUI) such as My Computer, Windows<sup>®</sup> Explorer, Control Panel, or Internet Explorer to see, access, and configure many of the devices that are integrated into the computer system. Host adapters, however, are typically configured at the system level through the basic

input/output system (BIOS) and not easily accessed, configured, or understood by the typical computer user.

SCSI host adapters contain electrically erasable programmable read only memory (EEPROM) chips which are programmed with configuration settings for the SCSI host adapter, and for the peripheral devices attached to the host adapter. When the computer boots up, the BIOS of the computer communicates with the EEPROM chip of the SCSI host adapter to determine what devices are connected to the host adapter and connected to the computer through the host adapter. The BIOS also determines the settings of the host adapter card and initializes the computer system in accordance with the settings. Once the boot sequence is complete and Windows® loads, the host adapter and the connected peripheral devices are set and no configuration settings or changes are possible for the host adapter or the peripheral devices as managed by the host adapter in the Windows® environment. In order to make any changes to the SCSI host adapter board settings, the user must shut down Windows® and access the SCSI host adapter through the BIOS.

Once Windows® has loaded, many system devices are accessible through GUIs such as My Computer, Control Panel, Windows® Explorer, and Internet Explorer as described above, and some configuration setting is possible, but such configuration is generally limited to computer system settings. By way of example, settings related to the computer system processing of certain devices can be modified in the Windows® environment. Such settings include memory use, interrupt setting, DMA channel, and the like. Some Windows® environments (*e.g.*, Windows NT™) also display that a host adapter is connected to the system and allows for system settings access, but does not provide for access to the settings for the host adapter itself, or for the peripheral devices connected to the host adapter.

Thus, when a user desires to access and configure, or trouble-shoot, a host adapter, the user must gain access through the BIOS prior to the Windows® operating system loading. While SCSI offers significant connectivity advantages, the current method of access and configuration of host adapters can limit flexibility when a user is unfamiliar with a computer system's BIOS, how to access the BIOS, and how to understand and change host adapter settings through the computer system BIOS.

In view of the foregoing, there is a need for a method and system to permit access to determine the presence and configuration of a host adapter, the presence and configuration of peripheral devices connected to the host adapter, and the ability to edit and manage the settings of the host adapter and connected peripheral devices. Such access should be easily understood and utilized by a user working in a Windows® environment to increase the flexibility and connectivity of a computer system. The method and system of access and ability to edit and manage host adapters and peripheral devices connected to host adapters should be configured to avoid the problems of the prior art.

### **SUMMARY OF THE INVENTION**

Broadly speaking, the present invention fills the aforementioned needs by providing methods, systems, and computer readable media for allowing access to manage host adapter configuration from a Windows® operating system. The invention presents a host adapter as any other system device presented in a plurality of graphical user interfaces, allowing for the configuration and management of the host adapter as well as any peripheral devices connected to the host adapter. It should be appreciated that the present invention can be implemented in numerous ways, including as a process, an apparatus, a

system, a device, a method, or a computer readable media. Exemplary embodiments of the present invention are described below.

In accordance with one aspect of the invention, a method for managing a configuration of a host adapter for a computer is provided. The method includes  
5 generating a graphical user interface which allows a user to access configuration settings of the host adapter, and then managing the configuration settings of the host adapter by using of the graphical user interface to create configuration changes. The configuration changes are saved to a file in a storage location. The method then provides for the rebooting of the computer, and reading the configuration changes saved to the file in the  
10 storage location during the reboot. The method further provides for the writing of the configuration changes to a nonvolatile memory of the host adapter of the computer, and then activating the configuration changes during the rebooting of the computer.

In accordance with another aspect of the invention, a method is provided for accessing and managing a configuration of a host adapter for a computer. The method  
15 includes generating a graphical user interface, and accessing and managing the configuration of the host adapter through the graphical user interface. The accessing and managing of the configuration includes making changes to the configuration. The method then provides for saving the changes to the configuration to a registry key. Next, a command is received to reboot the computer, and the method provides for executing the  
20 reboot command and initiating a reboot operation. The method further provides that, during the reboot operation, the changes to the configuration that were saved to the registry key are read, and then written to a nonvolatile memory of the host adapter of the computer.

In accordance with yet another aspect of the invention, a method for enabling graphical user interface driven modifications of settings in an EEPROM associated with a SCSI host adapter connected to a computer is provided. The method includes displaying a graphical user interface which provides a list of selectable configuration options, and receiving user selections of changes to the configuration. The method then provides for writing the user selections to a storage location, followed by initiating a reboot of the computer. Next, the method writes the user selections from the storage location to the EEPROM, and then completes the rebooting. The SCSI host adapter is configured to operate in accordance with the user selections.

In accordance with a further aspect of the invention, a computer readable media having program instructions for managing configuration settings of a SCSI host adapter for a computer is provided. Program instructions are provided for generating a graphical user interface which is configured to allow a user to access the configuration settings of the SCSI host adapter, and for generating a functional SCSI icon configured to provide direct graphical user interface driven access to enable configuration settings modifications. Further, program instructions are provided for selecting configuration settings modifications of the SCSI host adapter by way of the graphical user interface to create configuration changes. The configuration changes are saved to a file in a storage location. The program instructions then reboot the computer and read the configuration changes saved to the file in the storage location. Next, the program instructions include writing the configuration changes to a nonvolatile memory of the SCSI host adapter of the computer, and activating the configuration changes for the SCSI host adapter during the rebooting of the computer.

In accordance with still a further aspect of the invention, a computer readable media is provided having program instructions for accessing and managing a configuration of a host adapter of a computer. The program instructions include providing a graphical user interface which is configured to provide access to the configuration of the host adapter of the computer, and program instructions for managing the configuration of the host adapter of the computer by allowing a user to make configuration changes to the host adapter through the graphical user interface. The program instructions further provide for receiving the changes to the configuration of the host adapter and writing the changes to a registry key. The user is informed that a reboot operation is required for the configuration changes of the host adapter to be implemented, and program instructions provide the user with a reboot command and prompt the user to execute the reboot command. Further, program instructions are provided for receiving the reboot command and initiating the reboot operation. The configuration changes are read from the registry key, flashed to an EEPROM of the host adapter, and then the program instructions provide for completing the reboot operation by shutting down an operating system and starting a boot sequence.

The advantages of the present invention are numerous. One notable benefit and advantage is that the invention allows the average computer user the ability to see and manage the configuration of a host adapter of a computer system. Because the prior art host adapter management is BIOS-based, it is generally inaccessible and unknown to the average computer user. The present invention gives the host adapter the look and feel of any other computer system component, visible and accessible through the operating system.

An additional benefit is the ease of configuration using the present invention. By implementing the use of graphical user interfaces, the present invention allows configuration of the host adapter as well as the peripheral devices connected to the host adapter with selection boxes that a user can select or disable as desired. Further, the user  
5 can make configuration changes and then run diagnostic tests to verify performance with changes in configuration changes. Further, the present invention provides for simulation of configuration options such that a user can design a system configuration and evaluate the performance and compatibility prior to the actual installation of the hardware.

A further benefit is the ability to monitor host adapter performance using various  
10 tools provided by the present invention. Trouble shooting can be easily accomplished, and managed by telephone support without necessitating an on-site visit by tech support. Because the graphical user interface is familiar and comfortable to the average user, the ability to navigate and select various tools and support services of the present invention is available to all users, and can be easily evaluated and communicated over the telephone,  
15 internet, or other remote systems.

Other advantages of the invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

The present invention will be readily understood by the following detailed description in conjunction with the accompanying drawings, and like reference numerals  
5 designate like structural elements.

Figure 1 is an exemplary computer system in accordance with one embodiment of the present invention.

Figure 2A is a screen shot of a Windows® Control Panel GUI in accordance with one embodiment of the present invention.

10 Figure 2B shows the SCSI Control Panel GUI that results when the SCSI Control Panel icon is selected.

Figure 2C shows the Host Adapter 00 GUI that results when Host Adapter 00 is selected in the SCSI Control Panel GUI shown in Figure 2B.

15 Figure 3A illustrates the My Computer GUI in accordance with an embodiment of the invention.

Figure 3B illustrates yet another embodiment of the invention in which a SCSI Explorer icon is contained in and accessible through the Windows® Explorer GUI.

Figure 3C shows the resulting Windows® Explorer GUI in accordance with one embodiment of the invention with the SCSI Explorer icon expanded to display the  
20 connected host adapters, and Host Adapter 00 selected.

Figure 3D illustrates a general properties GUI of Host Adapter 00.

Figure 3E shows the bandwidth meter GUI in accordance with one embodiment of the present invention.

Figure 3F is a domain validation monitor GUI in accordance with one embodiment of the present invention.

Figure 3G shows the advanced configuration settings GUI in accordance with one embodiment of the invention.

5        Figure 3H shows a properties GUI for the hard drive connected to the host adapter shown in Figure 1.

Figure 3I shows a properties GUI for the CD-R optical device connected to the host adapter shown in Figure 1.

10       Figure 4A illustrates an Internet Explorer GUI in accordance with another embodiment of the present invention.

Figure 4B shows the Internet Explorer GUI connected through the World Wide Web to a manufacturer website in accordance with an embodiment of the invention.

Figure 4C shows the desk band across the bottom of the Windows® desktop in accordance with one embodiment of the invention.

15       Figure 4D shows an alternative embodiment of displaying the desk band as a tool bar in the Windows® environment.

Figure 5 shows a system diagram of the routes for accessing, configuring, managing, and monitoring the host adapter in accordance with one embodiment of the present invention.

20       Figure 6 is a flowchart diagram of the method operations performed for accessing and making changes to a host adapter in accordance with one embodiment of the present invention.

Figure 7 is a flowchart diagram of the method operations performed for accessing and making changes to a host adapter in accordance with another embodiment of the invention.

### **DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS**

5

An invention for a method and system for managing settings of a host adapter is disclosed. In the following description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be understood, however, to one skilled in the art, that the present invention may be practiced without some or all of these specific details. In other instances, well known process operations have not been described in detail in order not to unnecessarily obscure the present invention.

10

15

20

An exemplary computer system 200 in accordance with one embodiment of the present invention is illustrated in Figure 1. The computer system 200 includes a computer contained within a tower case 202, a display monitor 204, a keyboard 206 and a mouse 208. The computer contained within the tower case 202 includes a SCSI host adapter 210 with 4 connected peripheral devices. The peripheral devices include a hard drive 212, a CD-R optical media device 214, a CD-ROM optical media device 216, and a Jaz high volume storage device 218. The identified devices are representative of the many devices that might be connected to a computer, and should not be construed as all-encompassing or limiting. In one embodiment of the present invention, a SCSI host adapter 210 can provide connectivity for up to 30 peripheral devices to the computer system 200. Additional peripheral devices can include scanners, CD-R/W optical media devices, DVD drives, photographic devices, tape drives, and the like.

In a Windows® environment, access to edit and manage configuration settings of computer system 200 components is generally provided through a graphical user interface (GUI). By way of example, a display monitor 204 may provide for specialized settings for particular systems or applications, a mouse 208 can be adjusted for speed, sensitivity, or type of signal controlling mouse/cursor movement, and even keyboards 206 provide for configuration changes to include speed of character repeat, language used, and the like. In addition to device-specific configuration settings, system management of the devices allow for system configuration settings and management in the system utilization and processing of the various devices. System components can generally be accessed and settings or configuration can be changed and managed through such GUIs as My Computer, Control Panel, Windows® Explorer, Internet Explorer and the like.

Figure 2A is a screen shot of a Windows® Control Panel GUI 220 in accordance with one embodiment of the present invention. As is known, the Control Panel GUI 220 is one method to access system devices and configuration settings in the Windows® environment. Icons represent various system devices and parameters, and a user selects a particular icon to open a window or screen, another GUI, to access the configuration settings, parameters, and properties for the desired device or system parameter. In Figure 2A, configuration settings and properties for the display monitor 204 (Figure 1) are accessible by selecting the display icon 204a, the configuration settings and properties for the keyboard 206 (Figure 1) are accessible by selecting the keyboard icon 206a, and the configuration settings and properties for the mouse 208 (Figure 1) are accessible by selecting the mouse icon 208a.

Also illustrated and available for selection in the Control Panel GUI 220 illustrated in Figure 2A is a SCSI Control Panel icon 222. As will be described in greater

detail below, in one embodiment, the SCSI Control Panel icon 222 is one of several methods for a user to access the SCSI host adapter board 210 (Figure 1) configuration settings and properties, as well as the configuration settings and properties of each of the peripheral devices attached to the selected SCSI host adapter 210 (Figure 1). The SCSI Control panel provides such access to all SCSI host adapters that may be configured to the system. As can be seen in Figure 2A, the SCSI Control Panel icon 222 in Control Panel 220 provides the graphical representation of the SCSI host adapter as simply another system device, accessible to a user just as the display 204a, mouse 208a, keyboard 206a, and the other illustrated icons are system components and accessible to the user.

Figure 2B shows the SCSI Control Panel GUI 230 that results when the SCSI Control Panel icon 222 (Figure 2A) is selected. In Figure 2B, the SCSI Control Panel GUI 230 indicates there are three SCSI host adapters 210a, 210b, 210c configured to the exemplary system illustrated in the Control Panel GUI 220 of Figure 2A. By selecting the SCSI Control Panel icon 222 shown in Figure 2A, the SCSI Control Panel GUI 230 shown in Figure 2B is displayed. The SCSI Control Panel GUI 230 displays all SCSI host adapters configured to the system.

Figure 2C shows the Host Adapter 00 GUI 232 that results when Host Adapter 00 210a is selected in the SCSI Control Panel GUI 230 shown in Figure 2B. The Host Adapter 00 GUI 232 is another Control Panel GUI showing the devices connected to the selected host adapter. In Figure 2C, the user can see that a hard drive 212a, a CD-R optical device 214a, a CD-ROM optical device 216a, and a Jaz high volume storage device 218a are connected to the selected SCSI host adapter 210a (Figure 2B). The displayed devices correspond to the exemplary computer system 200 illustrated in Figure 1. As will be discussed in greater detail below, each of the devices displayed in the Host

Adapter 00 GUI 232 can be selected to access and manage the configuration settings and properties for the device.

As is known, the Windows<sup>®</sup> environment allows for a plurality of methods and modes of access to navigate and operate within the system. Figure 3A illustrates the My Computer GUI 240 in accordance with an embodiment of the invention. The My Computer GUI 240 is an alternative means of navigating within the Windows<sup>®</sup> environment. Similar to the Control Panel GUI 220 (Figure 2A), the My Computer GUI 240 provides a number of icons representing various regions and devices within the system. As shown in Figure 3A, these regions and devices include drive A with a 3 ½ inch floppy disk drive 242, a drive C with a main hard drive 244, an icon leading to the Control Panel 220a as illustrated in Figure 2A, and a SCSI Explorer icon 222a, among the various regions and devices available to a user for selection. By selecting the SCSI Explorer icon 222a, the user can navigate through additional GUIs similar to those GUIs described above in reference to Figures 2B and 2C to access and manage the configuration settings and properties of the selected host adapter and the peripheral devices attached to the host adapter. The SCSI Explorer icon 222a contained within the My Computer GUI 240 provides an alternative mode of access to the host adapter and connected peripheral devices, and provides a graphical representation of the host adapter as a system component accessible to the user.

Figure 3B illustrates yet another embodiment of the invention in which a SCSI Explorer icon 222a is contained in and accessible through the Windows<sup>®</sup> Explorer GUI 246. Windows<sup>®</sup> Explorer provides another method of navigating through the Windows<sup>®</sup> environment, and as can be seen in Figure 3B, the Windows<sup>®</sup> Explorer GUI 246 includes icons for My Computer 240a, the 3 ½ inch Floppy on Drive A 242, the main hard drive

on Drive C 244, the Control Panel 220a, the SCSI Explorer 222a, and other icons for the various drives, regions, and devices on the system. In one embodiment of the invention, the SCSI Explorer icon 222a is present and accessible in Windows® Explorer, and a user can navigate through the SCSI Explorer icon 222a to access the configured and attached host adapters, and the peripheral devices attached to the host adapters, to manage system and device configuration settings and properties.

Figure 3C shows the resulting Windows® Explorer GUI 246a in accordance with one embodiment of the invention with the SCSI Explorer icon 222a expanded to display the connected host adapters 210a, 210b, 210c, and Host Adapter 00 210a selected. With Host Adapter 00 210a selected, the connected devices are visible in the right pane of the displayed Windows® Explorer GUI 246a. As in the previous Figures, Host Adapter 00 210a is configured with a CD-R optical media device 214a, a CD-ROM optical media device 216a, a Jaz high volume storage drive 218a, and a hard drive 212a. In accordance with an embodiment of the invention, each of the connected peripheral devices 214a, 216a, 218a, 212a, as well as each host adapter 210a, 210b, 210c, is accessible through the displayed Windows® Explorer GUI 246a, or through any of the GUIs described above in reference to Figures 2A through 3B. Navigation through any of the above-described GUIs, or through the GUIs described in reference to Figures 4A-4D below, allow a user to access, edit, and manage the configuration and properties settings for a host adapter and any peripheral device connected to the host adapter.

Selection of the SCSI Explorer icon 222a in Figure 3C allows a user to navigate to the properties and configuration GUIs for the host adapters 210a, 210b, 210c, and for the peripheral devices 214a, 216a, 218a, 212a. Figure 3D illustrates a general properties GUI 250 of Host Adapter 00 210a (Figures 2B and 3C). Once a host adapter has been selected

from any of the Windows® navigation GUIs as described above, a properties and configuration GUI for the selected host adapter is presented. In Figure 3D, the properties and configuration GUI for Host Adapter 00 210a is represented with the general properties GUI 250 illustrated. A user can select from the tabs across the top of the GUI to display the general properties 250a, domain validation monitor 250b, bandwidth meter 250c, or any specialized additional pages 250d that may be present. By way of example, some host adapters have specialized features that may be accessed, in one embodiment of the invention, with the creation of additional pages 250d easily added to the properties and configuration GUI.

The general properties GUI 250 in Figure 3D identifies the host adapter by model and type, host adapter number, SCSI identification number and host adapter identifier, and provides general information about the selected SCSI host adapter. The "Advanced" button 250c navigates a user to an additional configuration setting screen discussed in greater detail below in reference to Figure 3G. The GUI further provides the standard Windows® settings selections of "OK" 250f, "Cancel" 250g, and "Apply" 250h. Figure 3D illustrates that the host adapter operates similarly to most other system components that, once connected, provides the computer system with general properties and identifying information that is accessible in the general properties GUI 250.

Figure 3E shows the bandwidth meter GUI 252 in accordance with one embodiment of the present invention. As shown, the bandwidth meter GUI 252 provides a graphical display of the bandwidth of the signal through the selected host adapter. The bandwidth meter GUI can be set to display the bandwidth of the signal currently through the selected host adapter by selecting the "Current" button 252k, or to display a graph of the bandwidth for a period of up to 24 hours by selecting the "History" button 252j. An

"I/O Planner" button 252m is further included to provide a planning tool to enable a user to design a system configuration prior to installing the hardware. The I/O planner button 252 provides a simulation of host adapter and peripheral devices system performance for a desired number and type of host adapters and devices. By way of example, a user can select the I/O Planner button 252 and input specific host adapters and/or peripheral devices. The I/O Planner then graphically demonstrates a simulation of the system and host adapter overall performance with the configuration as provided by the user. The bandwidth meter GUI 252 can be used to monitor and evaluate the performance of a host adapter, for trouble-shooting, and is accessed by selecting the bandwidth meter tab 252c at the top of the GUI as described above in reference to Figure 3D.

Figure 3F is a domain validation monitor GUI 254 in accordance with one embodiment of the present invention. Each time a peripheral device is attached to a host adapter, the host adapter optimizes the peripheral device performance based on available bandwidth to the host adapter and the capacity of the peripheral device. The domain validation monitor GUI 254 provides a visual monitor of device performance in accordance with one embodiment of the present invention, and can be used to verify the device is performing as advertised, or to trouble-shoot performance issues of devices connected to selected host adapters. The domain validation monitor GUI 254 is accessible by selecting the domain validation monitor tab 254b at the top of the GUI as described in reference to Figure 3D.

Figure 3G shows the advanced configuration settings GUI 256 in accordance with one embodiment of the invention. When a user selects the "Advanced" button on the general properties GUI 250 in Figure 3D, the advanced configuration settings GUI 256 is presented as shown in Figure 3G. Through the advanced configuration settings GUI 256,

a user can select from the various configuration settings as shown in Figure 3G. The available configuration settings are utilized to configure the actual host adapter board while in the Windows® environment. The settings displayed and configurable through the advanced configuration settings GUI 256 include those settings that in prior art are only accessible through the system BIOS, but in one embodiment of the present invention, the host adapter settings can be configured while operating in Windows®. The method of configuring the host adapter and attached peripheral devices is described more fully below in reference to Figures 6 and 7. One embodiment of the present invention provides an advanced configuration settings GUI 256 as illustrated in Figure 3G, allowing a user to select and configure a host adapter while in a Windows® environment just as a user can select and configure the various system components as illustrated in Figures 2A, 3A, and 3B.

Figures 3H and 3I show configuration GUIs for peripheral devices connected to a host adapter in accordance with one embodiment of the present invention. One embodiment of the present invention provides for accessing, configuration, and management of peripheral devices connected to a SCSI host adapter, in addition to the host adapter itself. Figure 3H shows a properties GUI 260 for the hard drive 212 connected to the host adapter 210 shown in Figure 1. The illustrated embodiment of the properties GUI 260 contains two pages or screens, GUIs, selectable from tabs 260a, 260b at the top of the properties GUI 260. In the hard drive example of Figure 3H, the general properties screen is displayed with device and performance information thereon. An "Advanced" properties 260c button is noted providing access to the system and device configuration settings for the hard drive, similar to the system and configuration settings described above in reference to the host adapter in Figure 3G.

Figure 3I shows a properties GUI 262 for the CD-R optical device 214 connected to the host adapter 210 shown in Figure 1. The embodiment of the CD-R optical device properties GUI 262 in Figure 3I is similar to the properties GUI 260 described in Figure 3H. In Figure 3I, the CD-R properties GUI 262 is the "Tools" GUI obtained by selecting the Tools tab 262b at the top of the screen. The "Tools" GUI 262 provides access to a plurality of utility software routines that utilize the various peripheral devices attached to the host adapter.

Figure 4A illustrates an Internet Explorer GUI 270 in accordance with another embodiment of the present invention. Yet another method of navigating the Windows® environment is with Internet Explorer. Figure 4A shows the Internet Explorer GUI 270. As is known, computer system navigation in the Windows® environment can be enhanced by using Internet Explorer to interact with a remote system across the World Wide Web. In Figure 4A, system host adapters 210a, 210b are visible on the left side of the Internet Explorer GUI 270. In Figure 4B, the Internet Explorer GUI 270 is shown connected through the World Wide Web to a manufacturer website. Host adapters 210a, 210b, 210c remain visible and selectable along the left side of the Internet Explorer GUI 270. An Internet Explorer Band 275 is shown expanded across the bottom of the Internet Explorer GUI 270, with additional applications and tools available for selection that are configured to access, manage, utilize devices connected to the installed host adapters. The Internet Explorer Band 275 provides yet another method of navigating through the plurality of GUIs available to access and manage the host adapters 210a, 210b, 210c as described in detail above with reference to Figures 2A-3I.

Figures 4C and 4D further illustrate the desk band 278, 278a in accordance with an embodiment of the invention. The desk band 278, 278a correlates to the Internet

Explorer Desk Band 275 (Figure 4B), without the Internet Explorer GUI 270 (Figures 4A-4B) open. In Figure 4C, the desk band 278 is shown across the bottom of the Windows® desktop. As described above, the desk band 278 provides another method of navigating to the host adapter GUIs. Figure 4D shows an alternative method of displaying the desk band 278a as a tool bar in the Windows® environment.

Figure 5 shows a system diagram 300 of the above-described routes for accessing, configuring, managing, and monitoring the host adapter in accordance with one embodiment of the present invention. The present invention provides access to a host adapter through the Windows® environment in one embodiment, and the WindowShell block 302 at the top of the system diagram 300 represents the Windows® operating system as the route to host adapter access. As described in detail above, the Windows® environment provides a plurality of methods of navigation within the operating system, and the second tier of the system diagram 300 identifies three methods that can be used to access the host adapter. Block 304 is the control panel extension module and includes the control panel GUI 220 as described above in reference to Figure 2A. Block 306 is the shell name space extension module and includes the my computer GUI 240 as described above in reference to Figure 3A and the Windows® Explorer GUI 246 as described above in reference to Figure 3B. The internet explorer extension module block 308 includes the internet explorer GUI 270 as described above in reference to Figure 4A, and the desk bands 275, 278, 278a illustrated in Figures 4B, 4C and 4D respectively.

Each of the blocks 304, 306 and 308 represent a different navigation method within the Windows® operating system shell, and either or all will provide a user access to the SCSI tools module block 310 in accordance with one embodiment of the

invention. The SCSI tools module block 310 represents all of the configuration, properties, and utilities GUIs described above in reference to Figures 3D-3I. The GUIs provide for user access, management, monitoring, configuration, modification, and meaningful use of host adapters and connected peripheral devices within the Windows® environment. The GUIs present host adapters and connected peripheral devices as additional computer system components with the look, feel, and implementation of integral system components. Methods of use of the invention are described in greater detail below in reference to Figures 6 and 7.

Figure 6 is a flowchart diagram 600 of the method operations performed for accessing and making changes to a host adapter in accordance with one embodiment of the present invention. The method begins with operation 602 in which a user is provided with a GUI that enables access to configuration data of a host adapter. The GUI exists and operates within the Windows® environment. Examples of such GUIs include My Computer, Control Panel, Windows® Explorer, Internet Explorer, and the like. As is known, when device configuration is accomplished through the system BIOS, it is accomplished by use of BIOS-level screens, text-only user interface. The user interface provided in operation 602 is a GUI that exists and operates within the Windows® operating system. The Graphical User Interface is known to be much more immediate and easier to use than older text-only User Interface.

The method continues with operation 604 in which a temporary configuration file is provided. When changes are made to a host adapter, the host adapter cannot be actively processing data from peripheral devices or the system. Desired configuration or settings changes are therefore written to a configuration file in a storage location that is accessible to the BIOS during system boot. The storage location can be one of a location

on a hard drive, some memory on the mother board, and some memory on the host adapter. By way of example, the storage location might be a memory chip configured to receive the host adapter changes and identified by the BIOS to be read for any configuration changes. During the boot operation, the system is initially configured by the BIOS, and in one embodiment of the present invention, the BIOS reads the desired host adapter configuration settings during the boot sequence from the temporary configuration file in a storage location as provided in operation 604.

The method proceeds with operation 606 in which host adapter configuration or settings changes are received from a user, and the changes are written to the temporary configuration file. By way of example, the user can navigate through any of the above described GUIs to a host adapter advanced settings GUI. The user selects desired host adapter settings, and then saves the settings. When the settings are saved, they are written to the temporary configuration file.

The method then advances to operation 608 where the user is informed that the new settings will not be available until reboot. As described above, the configuration of a host adapter cannot be changed while the host adapter is processing data, or any of the connected peripheral devices are active and processing data. In operation 608, the user is prompted that a reboot is necessary to implement the requested changes and, in one embodiment, provides the user with a prompt to initiate a reboot.

In operation 610, the reboot command is received, and the reboot is initiated. By way of example, the user might be provided with a system query to initiate reboot. If the user selects "Yes," the reboot command is received and executed. As is known, the system then initiates a shut down of all system devices, including a final processing of

any active data. The system shuts down all peripheral devices, the Windows® operating system, and begins system initialization with the BIOS.

Next, in operation 612, the system BIOS executes the boot sequence. During the boot sequence, the system BIOS goes to the storage location and reads the temporary configuration file provided in operation 604. The configuration settings for the host adapter that were written to the temporary configuration file are then written to the EEPROM of the host adapter.

Finally, in operation 614, the system reboot is completed with the new settings activated. The system is initialized in accordance with the new settings, and the method is done.

Figure 7 is a flowchart diagram 700 of the method operations performed for accessing and making changes to a host adapter in accordance with another embodiment of the invention. The method begins with operation 702 in which a user is provided a GUI for accessing and managing a SCSI host adapter. As described above in reference to figure 6, the GUI provided is a high level GUI, and operation 702 is identical to operation 602 as described above.

The method continues with operation 704 in which configuration data is received from a user. The user makes the desired settings or configuration changes through the provided GUI, such as the advanced settings GUI for the selected host adapter. When the user saves the desired changes, the configuration or settings changes are saved to a registry key. The registry key is a dedicated operation that is read and executed by system or device drivers during specified operations as will be described below.

Next, the method executes a reboot procedure in operation 706. As described above in reference to Figure 6, any host adapter configuration or settings changes cannot be implemented while the host adapter is actively processing data, or any data is being processed by connected peripheral devices. In one embodiment, the user is prompted that a reboot is required, and provided with a command to execute a reboot. In operation 5 706, the user has selected, and the system executes the reboot command. In executing a reboot, the system begins to shut down all applications and peripheral devices.

In operation 708, the system continues with the shut down sequence. Any active data is finally processed, the peripheral devices are shut down, all applications are closed, and the system prepares to shut down the operating system. 10

Next, in operation 710, the system executes final Ring 0 or kernel mode operations just prior to shutting down the operating system. Device drivers in Ring 0 execute programmed operations in accordance with operating system parameters, and in operation 710, a device driver checks the registry key for configuration data. If data is present, the data is processed as described below. If no data has been written to the designated registry key, no new settings or configuration data for the host adapter will be processed. In Figure 7, configuration data was written to a registry key in operation 704. This configuration data is read in operation 710, and the method advances to operation 712. 15

In operation 712, the device driver writes or “flashes” the configuration data to the EEPROM of the SCSI host adapter. At this point in the shut down procedure, all peripheral devices have been shut down, all applications have been closed, and no data is being processed by the computer system except for the device drivers at Ring 0 20

performing the final sequences of the operating system shut down. Therefore, it is possible to write the configuration settings to the EEPROM of the SCSI host adapter at this point. The host adapter configuration or settings information data read from the registry key is thus written to the EEPROM of the SCSI host adapter in operation 712.

5           The method advances to operation 714 where the system is finally shut down and the reboot begins. As described above, the BIOS executes the system initialization. The BIOS reads the host adapter configuration settings from the EEPROM and initializes the system in accordance with those settings. The user, having changed the settings through a GUI in the Windows® environment, is presented with a system in accordance with the  
10   new settings, and the method is done.

          The present invention may employ various computer-implemented operations involving data stored in computer systems. These operations are those requiring physical manipulation of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined,  
15   compared, and otherwise manipulated. Further, the manipulations performed are often referred to in terms, such as producing, identifying, determining, or comparing.

          Any of the operations described herein that form part of the invention are useful machine operations. The invention also relates to a device or an apparatus for performing these operations. The apparatus may be specially constructed for the required purposes,  
20   or it may be a general purpose computer selectively activated or configured by a computer program stored in the computer. In particular, various general purpose machines may be used with computer programs written in accordance with the teachings herein, or it may be more convenient to construct a more specialized apparatus to perform the required operations.

The invention can also be embodied as computer readable code on a computer readable medium. The computer readable medium is any data storage device that can store data, which can thereafter be read by a computer system. Examples of the computer readable medium include read-only memory, random-access memory, CD-ROMs, CD-Rs, CD-RWs, magnetic tapes, and other optical data storage devices. The computer readable medium can also be distributed over network coupled computer systems so that the computer readable code is stored and executed in a distributed fashion.

Although the foregoing invention has been described in some detail for purposes of clarity of understanding, it will be apparent that certain changes and modifications may be practiced within the scope of the appended claims. Accordingly, the present embodiments are to be considered as illustrative and not restrictive, and the invention is not to be limited to the details given herein, but may be modified within the scope and equivalents of the appended claims.

*What is claimed is:*